FORD TRUCKS 3542M EURO6





Basic Features		
Vehicle Type	Mixer	
Axle	6x4	
Emission	Euro 6	
Cabin Type	Day Cab	
Wheelbase (mm)	3800	

Liigine	
Type	Ecotorq 12,7 liters
Displacement (cc)	12740
Bore x Stroke	130 mm x 160 mm
Power	420 PS (308,9 kW) / 1800 rpm
Torque	2150 Nm / 1000-1300 rpm
Compression Ratio	17 +/- 0,5 : 1
Oil Filling Volume	50 L

Transmission	
Clutch	430 mm Single Disc
Manuel Transmission / Ratios (1. gear - 16. gear)	ZF 16S 2230 (13,805-0,836)
Automated Transmission / Ratios (1. gear - 12. gear)	ZF 12 TX 2210 (16,688-1)

Automated Transmission / Ratios (1. gear - 12. gear) Steering

Coolant Volume

Chassis

Power Assisted Single Circuit

57 L (77 L with Intarder)

Chassis Thickness	10 mm with Local Reinforcement			
Chassis Strength	500 MPa			
Suspension (Front / Rear)	90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension			
Axle	Hub Reduction			
Axle Ratio	4,08 / 3,57			
Tyres	315/80 R 22,5			
Wheel Rim	22,5 x 9 Steel			

Wheel Rim	22,5 x 9 Steel		
Braking System			
Brakes (Ø mm x mm length)	430 x 45 - Disc Brakes		

Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater Braking System Engine Brake Power max. 320 kW (Engine Level) Intarder Power max. 600 kW / continuous 160 kW

Electrical System Battery 24V, 2 x 12V 150 Ah

Alternator / Starter Motor 130 A / 6,5 kW Tanks 315 L Steel Fuel Tank SCR Tank 55 L



Dimensions (mm)	
Front Overhang	1500
Wheelbase	3800
Overall Length	8290
Distance Between 2 nd and 3 th Wheel Centers	1350
Overall Cab Length	1820
Overall Vehicle Height	3168
Overall Vehicle Width (Excluding Mirrors)	2540
Chassis Width	770
Rear Overhang	1640
Useful Chassis Length	5885
Chassis Height-Front	1126
Chassis Height-Rear	1148
Ground Clearance-Front	369
Ground Clearance-Rear	294
Turning Radius	8790

Weights (kg)	1. Axle	2. Axle	3. Axle	Total
Technically Permissible Weights	8000	13400	13400	34800
Kerb Weight	5150	2426	2211	9787
Payload	2850	10974	11189	25013
GVM (Legal)	7500	9500	9500	26000

STANDARD EQUIPMENT

- Air Conditioner
- AM/FM/Aux In/USB/Bluetooth (Radio with Bluetooth)
- 4 Points Independent Cab Suspension for Day Cab
- Engine Driven PTO & Interior Control Unit
- Cruise Control
- Engine Brake
- Disc Brake
- Electrically Operated Windows
- Heated and Electrically Operated Side Mirrors
- Electrically Operated Headlamp Leveling
- Rake and Reach Adjustable Steering Column
- Electrically Operated and Heated Side Mirrors
- Lumbar Support
- Front and Rear Vehicle Antiroll Bars
- Anti-Lock Brake System (ABS)
- Continuous Wear Sensor
- Immobilizer
- Single Key with Remote Control and Central Locking
- Home Safe Light
- Approach Light
- Differential Lock
- Digital Tachograph
- Front Towing Hooks (Double Hook)
- Oil Pan Protection
- Ventilation Roof
- Short Bumper

OPTIONAL EQUIPMENT

- Transmission Offset (Double Gear) PTO without Flange (includes Power Take off Control Unit)
- Transmission Direct (Double Gear) PTO with Flange (includes Power Take off Control Unit)
- Automated Transmission
 (with Normal Mode, Off-Road Mode, Rocking Mode)
- Intarder
- ADR Pack
- Low Roof Sleeper Cab with Single Bed
- Auxiliary Cabin Heater (Wet Type)
- Cold Pack with Wet Type Cab Heater and 225 Ah Battery
- Cold Pack with Dry & Wet Type Cab Heater
- Power Cab Tilting
- Switchable Air Compressor for Improved Fuel Economy
- Transmission Driven PTO Options & Interior Control Unit
- Rubber Suspension (28T)*
- Manually Operated Sunroof
- Dual Passenger Seat
- Automatic Traction Control (ATC)

^{* 206}kg lighter compared to standard suspension vehicle.